

BABY LOCK SEWING ACCESSORIES

Adjustable Guide Foot

(BLQ2-AGF)


Instructions

For projects that require the utmost accuracy, such as garment sewing, topstitching or piecing the perfect quilt, this foot comes prepared to help. The built-in ruler with an adjustable guide is perfect for keeping your measurements precise at all times.

INSTRUCTIONS:


Removing the presser foot

Raise the presser foot (a).



Attaching the presser foot

Lower the presser foot holder (b) until the notch (c) is directly above the pin (d). Lower the presser foot holder (b) and the presser foot (e) will engage automatically.



The Precision Dual-Feed Quilting System (PDQ) feeds the fabric from the top and bottom simultaneously to ensure matching of the fabric layers, used for quilting layers of fabric and batting, and when matching checked, striped or plaid fabrics.

To Activate and Deactivate the Precision Dual-Feed Quilting System (PDQ)



To activate the PDQ system, raise the presser foot. Lower the PDQ mechanism slowly and swing the PDQ mechanism forward under the back of the presser foot until it is engaged and stays in the system. To deactivate the PDQ system, raise the presser foot, pull down on the mechanism and swing it to the rear then raise the PDQ up.



FOR THE LOVE OF SEWING

1. Remove the all-purpose foot. Attach the Adjustable Guide foot and engage the PDQ.
2. Adjust the grey guide to the desired distance. Use the red marking lines on the foot to reference 3/8", 1/2", 5/8", 3/4", 7/8", 1", 1-1/8" distances from the needle.
3. Place the edge of the fabric aligned with the grey guide on the Adjustable Guide Foot.
4. Lower the presser foot. Select the desired stitch. Sew at a consistent speed.



FOR THE LOVE OF SEWING

800-422-2952

www.babylock.com