

Blindstitch foot

#L19



Information

Purpose

- To sew invisible hems in medium-weight to heavy fabrics.
- To sew ladder stitch hems.

For your safety

Before using this accessory, please read the instruction manual at hand as well as the instruction manual of your machine carefully.



Application

To sew invisible hems

- > Select a 3-thread overlock stitch wide (LN) and thread the machine.
- > Adjust the stitch length to 3.5 – 4.5 mm.
- > Reduce the needle thread tension slightly.
- > Position the guide of the presser foot to 1 mm on the right of the needle.
- > Mark the hem depth (wrong side on wrong side) and iron the hem.
- > Fold the hem back so that the lower fabric edge lies on the right next to the folded edge. (Fig. 1)
- > Place the fabric under the presser foot and push the folded edge against the guiding plate of the presser foot. (Fig. 2)
- > Sew a few stitches. In doing so, make sure that the needle scarcely stitches the folded edge. If necessary, adjust the guide on the presser foot.
- > Sew the hem.



Sewing a ladder stitch hem

- > Select a 3-thread flatlock stitch wide (LN) and thread the machine.
- > Adjust the stitch length to 2.5 – 4.5 mm.
- > Position the guide of the presser foot in the middle between the needle and the knife.
- > Mark the hem depth (wrong side on wrong side) and iron the hem.
- > Fold the hem back so that the lower fabric edge lies on the right next to the folded edge. (Fig. 3)
- > Place the fabric under the presser foot and push the folded edge against the guiding plate of the presser foot. (Fig. 4)
- > Sew a few stitches. Check, whether the seam can be stretched flat easily. If the seam puckers, position the guide on the presser foot closer to the needle. (Fig. 5)
- > Sew the hem.



Tip:

- > For stretch fabrics, use the 2-thread flatlock seam wide (LN).



You can find further information at:
www.bernina.com